







Product Code	JCS-WHT-2400WP
Description	Single Piece Slim In-wall Cistern with Wall Mounting Frame, Installation Kit and "P-Type" Drain Pipe
	Connection Set for Wall Hung WC (without Flush Control Plate)
Flow Rate	3.0/6.0 LPF
Features	• Tank body: Strong 80 mm thick High-density polyethylene (HDPE) 'Single-piece' body.
	• Anti-Condensation Lining: Anti condensation lining of 6mm thick wall takes care of temperature
	change.
	• Inlet & Outlet Valves: Inlet valve has a special rotary structure which gives out low noise & anti
	siphon function. Both valves (Inlet & outlet) are WARS approved.
	• Working Pressure: 0.3-10 bar (1.0 to 3.0 bar is recommended with clear, non-aggressive water
	supply)
	• Life Cycles of Mechanism: The lifetime of sea water test and dirty water test have passed 100,000
	cycles
	• Flush Control Plates: ABS made chrome plated flush control plates which is compatible for Single
	Piece Slim in-wall Cistern (JCS-WHT-2400WP)
	Wall Mounted Frame: oxford blue Powder coated steel frame.
	• Water inlet: ½" water supply connection from top.
	• Flush volume: Factory setting 6.0~3.0 litres, Eco adjustable: 4.0~2.0 litres (Only for WC pans
	designed for low volume flushing).
Application	• For installation of a wall-hung WC with bolt fixing set at 180 or 230 mm centres
	Solid pre-wall installation system for brick & solid walls
	For installation in a load bearing stud wall.
	Not suitable for installation in a drywall

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.