

SLS-WHT-6951JUF

SPECIFICATION DATA SHEET

PF	เดกเ	UCT	DFT/	AII S

THOUGH PENNING					
Manufacturer :	Jaquar	Туре:	Wall hung WC (water closet)		
Range	Solo	Flush valves	Regular, Dual & I Flush advantages		
Colour:	White	Material:	Ceramic - Vitreous China		
Outlet	Vertical	BOM doc.NO.	JSW/12/2017/0123A		
	T				

Technical Details: Internal diameter of inlet hole Ø 58 + 2 - 1 mm

External diameter of outlet hole Ø 100 +5 -2 mm


ARTICLE NAME: WALL HUNG WC









TECHNICAL DIMENSIONS







BACK VIEW

ALL DIMENSIONS ARE IN MM. (TOLERANCE ± 5 MM)

PRODUCT DIMENSIONS				USP			
Length (mm)	Width (mm)	Height (mm)	Net weight (kg)	Day sine with he haild ich aline cook cause. Anti name alone			
365	515	390	22.90	Box rim with In-build jet , slim seat cover , Anti germ glaze			
	ACCESSORIES PROVIDED						
UF soft Close seat cover				SLS-WHT-6103UF			
Inlet & Outlet gasket				ZPS-WHT-GK01			
ACCESSORIES RECOMMENDED							
Rag bolt				ZPS-SNS-RB01 & ZPS-MST-RB02			
Concealed cistern model no				JCS-WHT-2400S,2400FS,2400WS			





CARE AND CLEANING GUIDELINES

- * Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.
- \bigstar The product is heavy and it is recommended that two persons hold it while it is being fixed.
- ★ Carefully inspect the new product for damage before installation.
- $\bigstar \ {\it Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.}$
- ★ Risk of external leakage. Do not lift or rock the bowl after placement.
- * Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- \bigstar Do not allow cleaners to sit or soak on the product.
- ★ Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
- \bigstar Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- ★ Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.
- ★ Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.

CERTIFICATION

Compliance: IS 2556.2:2004, IS 2556.1:1994, EN 997:2012+A1

All technical dimensions are in accordance to British standards, Bureau of Indian Standards

An econical annensions are in accordance to British standards, baread of malan standards								
PACKAGING DETAIL			LOADING PALLET DETAIL					
Length (mm)	Width (mm)	Height (mm)	Gross Weight(kg)	Length (mm)	Width (mm)	Height (mm)	No	of pieces on pallet
535	445	420	26.00	1140	1140	2285		16
J _P								
Prepared By		Controlled By		Verified By		Approved By		
Designer		Quality control		Product Manager		Sanitaryware Head		
Date								
Revision/Version	1	•		Plotter Updated on	Month	10-Jul	Year	2018