



Product Code	SNR-CHR-51011
Description	Sensor Faucet for Wash Basin Deck Mounted Complete with Control Box (Battery Operated)
Water Supply	Cold and hot water (2 inlets)
Water Temperature	5 °C - 65 °C
Inlet Water Connection	1/2"BSP / 15mm
Recommended Water Pressure	0.5 Bar - 6.0 Bar
Flow Rate	12.99 LPM @ 3 bar
Flow regulator	By using flow regulators (Product should be ordered with suffix as G-2.5 LPM, GA-6.0 LPM, GB-8.0 LPM, GC-13.0 LPM, GD-3.8 LPM & GE-1.3 LPM @ 3.0 Bar pressure) one can regulate the flow rate.
Recommended Water Pressure	0.5 Bar - 6.0 Bar
Material Composition Specification in Percentage	Brass Ingots as per IS:1264-1997 Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total Impurity (0.0-2.0), Zn (Remainder) Brass Rod as per IS:319-1989
	Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)
Solenoid Valve Specification	Operating pressure 0.5 - 6.0 bar Nominal Voltage : 6 Volt DC IP67 Protected : Very robust, reliable solenoid valve Low power consumption : Bi-stable pulse controlled
Electronic Parameter Setting Procedure	IR Touch ( No need of remote controlle
Adjustable Parameters	Detection Range : 1 - 8 level, default : 6, Follow up Time : 1 - 10 seconds, default : 1-2 Second In line purge feature : (Range - off, 12hrs ,24 hr, 48 hrs), default : off
Power Source	6 Volt Battery - Duracel CR-P2 Ultra Lithium 223 , 1400mAh
Water Tightness	10 Bar (Pass)
Pressure Resistance	15 Bar (Pass)
Finish	Plating: Nickel-10.0 micron Chromium-0.3 micron Salt Spray (500 hrs + Validated) Adhesion (Pass)
Aerator Size	WRAS, ACS Approved (M 24X1)
Available Color Finishing	CHROME (CHR)
DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/or countries. Jaquar reserves the right to make the necessary amendments at any time without prior notice.	