

ARS-WHT-39951UFSM

SPECIFICATION DATA SHEET

DRODUCT DETAILS

PRODUCT DETAILS								
Manufacturer :	nge Aria		Wall hung WC (water closet)					
Range			Regular, Dual & I Flush advantages					
Colour:			Ceramic - Vitreous China					
Outlet	Vertical	BOM doc.NO.	JSW/01/2018/0041					


Internal diameter of inlet hole Ø 58 +2 -1 mm Technical Details: External diameter of outlet hole Ø 100 +5 -2 mm


ARTICLE NAME: WALL HUNG WC






TECHNICAL DIMENSIONS







BACK VIEW

ALL DIMENSIONS ARE IN MM. (TOLERANCE ± 5 MM)

PRODUCT DIMENSIONS				USP				
Length (mm)	Width (mm)	Height (mm)	Net weight (kg)	Box Rim design with deep sump for efficient flushing, Slim seat cover, Anti germ				
360	575	360	30.50	glaze. Best suitable for bigger Bathrooms				
	ACCESSORIES PROVIDED							
UF Soft Close Slim Seat cover				ARS-WHT-39101UF				
Inlet & Outlet gasket				ZPS-WHT-GK01				
Side cap				ZPS-WHT-SC01				
ACCESSORIES RECOMMENDED								
Rag bolt				ZPS-MST-RB07				
Concealed cistern model no				ICS_WHT_2400S 2400ES 2400WS				






CARE AND CLEANING GUIDELINES

- * Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation
- ★ The product is heavy and it is recommended that two persons hold it while it is being fixed.
- \bigstar Carefully inspect the new product for damage before installation.
- \bigstar Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.
- ★ Risk of external leakage. Do not lift or rock the bowl after placement.
- ★ Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- ★ Do not allow cleaners to sit or soak on the product.
- ★ Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
- ★ Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- 🖈 Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.
- ★ Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.

CERTIFICATION

Compliance: IS 2556.2:2004, IS 2556.1:1994, EN 997:2012+A1:MS 1522:2015/CE









PACKAGING DETAIL				LODING PALLET DETAIL				
Length (mm)	Width (mm)	Height (mm)	Gross Weight(kg)	Length (mm)	Width (mm)	Height (mm)	No of pieces on pallet	
433	398	580	35.50	1140	1140	2285	16	





JP							
Prepared By	Controlled By	Verified By		Approved By			
Designer	Quality control	Product Manager		Sanitaryware H	ead		
Date							
Revision/Version 1	•	Plotter Updated on	Month	22-Aug	Year	2019	