

### SLS-WHT-6851S220PP

#### SPECIFICATION DATA SHEET

#### PRODUCT DETAILS


PRODUCT DETAILS						
Manufacturer :	Jaquar	Туре:	Single piece-WC (S trap )			
Range	Solo	Outlet	Horizontal			
Colour:	White	Material:	Ceramic - Vitreous China			
Technical Details:	External diameter of outlet Ø 80 mm	BOM doc.NO.	JSW/12/2017/0126			
	Horizontal distance between the wall line and the centre line of the waste outlet hole ≤ 220 mm					


## ARTICLE NAME: SINGLE PIECE - WC





### TECHNICAL DIMENSIONS





ALL DIMENSIONS ARE IN MM. (TOLERANCE ± 5 MM)

PRODUCT DIMENSIONS				USP				
Length (mm)	Width (mm)	Height (mm)	Net weight (kg)	Dev Disservish Devel Fleiching - Auti gegen des				
360	640	680	35.55	Box Rim with Dual Flushing,, Anti germ glaze				
	ACCESSORIES PROVIDED							
	PP soft Cl	ose seat cover		SLS-WHT-6103PP				
	Floor f	ixing screw		ZPS-SNS-FB02				
	W	ax Seal		ZPS-WHT-1401				
CARE AND CITAMING CHIPPINES								

- CARE AND CLEANING GUIDELINES

  ★ Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter
- $\bigstar$  The product is heavy and it is recommended that two persons hold it while it is being fixed.
- $\bigstar$  Carefully inspect the new product for damage before installation.
- $\bigstar$  Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.
- $\bigstar$  Risk of external leakage. Do not lift or rock the bowl after placement.
- $\bigstar$  Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- ★ Do not allow cleaners to sit or soak on the product.
- ★ Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
- ★ Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- ★ Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.
- ★ Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.

# CERTIFICATION

Compliance: IS 2556.2:2004, IS 2556.1:1994, EN 997:2012+A1, BS EN 14124:2004/CE

All technical dimensions are in accordance to British standards, Bureau of Indian Standards





	PACKAGING DETAIL			LOADII	NG PALLET DETAIL		
Length (mm)	Width (mm)	Height (mm)	Gross Weight(kg)	Length (mm)	Width (mm)	Height (mm)	no of pieces on pallet
650	385	685	41.95	1140	1140	2285	12





<u> </u>									
Prepared By		Controlled By		Verified By		Approved E	Зу		
Designer		Quality control		Product Manager		Sanitarywa	re Head		
Date									
Revision/Version	1			Plotter Undated on Moi	nth	10-Jul	Year	2018	