

KUS-WHT-35935

SPECIFICATION DATA SHEET

| PRODUCT DETAILS | | | | | | |
|-----------------|--------------------------------------|-------------|--------------------------|--|--|--|
| Manufacturer : | Jaquar | Туре: | Table top basin | | | |
| Range | Kubix | Colour: | White | | | |
| Outlet | Horizontal | Material: | Ceramic - Vitreous China | | | |
| | ID of waste outlet hole 45 Ø+2 -1 mm | BOM doc.NO. | JSW/12/2017/0016 | | | |

Technical Details: Diameter of Tap hole 35 +2-1 mm


Horizontal distance between the center line of the tap hole and the center line of the waste outlet hole ≤ 146 mm


ARTICLE NAME: TABLE TOP BASIN





TECHNICAL DIMENSIONS





TOP VIEW

ALL DIMENSIONS ARE IN MM. (TOLERANCE ± 5 MM)

| PRODUCT DIMENSIONS | | | | USP | | |
|--------------------|------------|-------------|-----------------|--|--|--|
| Length (mm) | Width (mm) | Height (mm) | Net weight (kg) | Rectangular shape with tap hole and anti germ glaze, can also be used as | | |
| 585 | 420 | 140 | 16.8 | wall hung basin. | | |

- CARE AND CLEANING GUIDELINES

 ★ Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.
- \bigstar The product is heavy and it is recommended that two persons hold it while it is being fixed.
- \bigstar Carefully inspect the new product for damage before installation.
- \bigstar Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.
- \bigstar Risk of external leakage. Do not lift or rock the bowl after placement.
- * Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- \bigstar Do not allow cleaners to sit or soak on the product.
- 🖈 Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
- \bigstar Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- ★ Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.
- ★ Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.

CERTIFICATION

Compliance: IS 2556.4:2004, IS 2556.1:1994, BS EN 14688 :2015/CE
All technical dimensions are in accordance to British standards, Bureau of Indian Standards





| PACKAGING DETAIL | | | | LOADING PALLET DETAIL | | | | |
|------------------|------------|-------------|------------------|-----------------------|------------|-------------|------------------------|--|
| Length (mm) | Width (mm) | Height (mm) | Gross Weight(kg) | Length (mm) | Width (mm) | Height (mm) | no of pieces on pallet | |
| 580 | 430 | 150 | 17.80 | 1140 | 1140 | 2285 | 52 | |





| Prepared By | | Controlled By | Verified By | | Approved By | | |
|------------------|---|-----------------|--------------------|-------|-------------------|------|------|
| Designer | | Quality control | Product Manager | | Sanitaryware Head | | |
| Date | | | | | | | |
| Revision/Version | 1 | | Plotter Updated on | Month | 10-Jul | Year | 2018 |